



POLIPLEX D3

WATER-RESISTANT VINYL ADHESIVE FOR FLOATING PLYWOOD AND PREFINISHED PARQUET FLOORS

FOR PROFESSIONAL USE ONLY

DESCRIPTION AND USAGE:

Water-resistant water emulsion vinyl adhesive in bottles with applicator nozzles for adhering male/female elements of floating floors in wood and plywood and elements in wood, chipboard and laminated wood panels. Complies with EN 14293. Water resistance class D3 (EN204/205).

PRODUCT CHARACTERISTICS:

Appearance:	viscous liquid
Colour:	white, clear once dry
Chemical base:	vinyl resins in water emulsion
Specific weight:	1.1 g/cm ³
Dry residue:	52%
Viscosity:	15,000 mPa.s
Dilution:	not necessary - ready to use
Application:	using applicator nozzle on bottle
Yield:	0.025 kg/linear metre (0.1-0.2 kg/m² if used for adhering and joining wooden elements)
Application temperature:	from +10°C to +30°C
Working time:	approx. 5-10 min.
Ready for foot traffic:	approx. 6 hours
Setting time:	approximately 24 hours.
Storage temperature:	from +10°C to +25°C
Storage shelf life:	12 months in original, unopened containers
Cleaning:	with water, while product is still fresh
Usage:	indoor
Suitable for wheelchairs:	YES
Suitable for heated underfloors:	YES
Safety instructions:	See safety data sheet
Packaging:	0.5 l bottles with applicator nozzle (box of 12 bottles)

INSTRUCTIONS FOR USE: The elements to be assembled must fit together perfectly and must be clean, in good condition and completely free of release agents such as oils, waxes, grease or dust. Maximum permissible moisture content:

- 2% for cement substrates or 1.8% with underfloor heating.

- Plaster or anhydrite screed substrates 0.5%, or 0.3% with underfloor heating.

Check that there are no signs of rising damp. To seal joints, dispense the product from the applicator nozzle on the bottle cap to form a continuous bead on the upper surface of the male side. To adhere joints, dispense the product to form a continuous bead on the female side of the slat, then assemble the elements immediately and keep pressed together for approximately 15 minutes. Remove any excess product immediately with a damp cloth. This product will not stain the wood.

OTHER INFORMATION: The application and adhesion times indicated in the product characteristics are for an ambient temperature of +20°C and a relative air humidity of 50%. Acclimatise the adhesive and the wood to ambient conditions before use.

INSTRUCTIONS FOR SAFETY AND DISPOSAL: Read the relative product safety data sheet before use. During usage, ensure adequate ventilation, protect the hands with MAGIC PELL cream and observe all applicable safety regulations. Do not dispose of residual product on soil, in surface water or in drains. When disposing of the product and other waste produced during usage, comply with the terms of Italian Law Decree 152/2006 and subsequent modifications (Unified Environmental Law). For more information, contact our technical support service. The contents of this sheet replace and supersede the contents of the previous edition.

NOTE: The information given herein is based on our extensive theoretical and practical knowledge. However, as it is impossible to go into exhaustive detail, the contents of this sheet are not binding in nature. Please contact our technical service in case of any doubt.